ichemco
Developing Chemical Excellence

member of Afera

CERTIFIED MANAGEMENT SYSTEMS
CERTIQUALITY
UNI EN ISO **9001:2015**
UNI EN ISO **14001:2015**
UNI ISO **45001:2018**

S.L. 60

(Provisional)

Description

S.L..60 is an acrylic latex in anionic water emulsion. The product is APEO free. Tg = -11°C

Application

S.L..60 can be used as binder for textile, paper, etc without residual tack.
It has a very soft hand after drying. Applied on fabrics, it is resistant to washing and rubbing.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	45±1
3. Brookfield Viscosity 25°C	mPa.s	50 - 200 (1)
8. pH		6 - 7
Solvents		water

(1) No 1 RV; 20 RPM

Handling

The product can be applied with: Mayer bar, foulard, rotogravure, air knife and, once thickened, with blade coating.

Packaging

The product is supplied in plastic drums (120 kg); IBC containers (1000 kg).

Storing

S.L..60 must be stored at temperature between +5 and +40°C .

Use within 6 months from production date (unopened and in the original packaging).

Build date 11 Sep 2025

Above information is reliable, but does not constitute warranty.

ICHEMCO srl
via 11 Settembre, 5 - 20012 CUGGIONO (MI) - ITALY
Phone: +39 02 97243.1 - info@ichemco.it - www.ichemco.it