Tackifier 765

(Provisional)

Description

TACKIFIER 765 is a solvent-free, water borne tackifier dispersion. It is APEO free. The resin component is a high quality disproportionated rosin ester, designed to provide very good adhesive performance to a wide range of substrates.

Ring & Ball value of the base resin = 64°C approx.

Application

TACKIFIER 765 is primarily intended to enhance the pressure sensitive adhesive properties of polymeric latices, such as acrylates or SBR used in the field of self adhesive tapes and labels.
TACKIFIER 765 improves adhesion to high and low energy substrates.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	50±1
3. Brookfield Viscosity 25°C	mPa.s	100 - 900 (1)
8. pH		7 - 8
Solvents		water

(1) No 1 RV; 20 RPM

Packaging

The product is supplied in IBC containers (1000 kg).

Storing

Protect from freezing: containing no freeze/thaw stabilizers, TACKIFIER 765 coagulates irreversibly upon freezing.
Must be stored at temperature between +5 and +40°C .
To prevent evaporation and subsequent formation of coarse particles, keep containers or drums closed.

Use within 6 months from the date of manufacture (unopened and in the original packaging).

Use within 9 months from production date (unopened and in the original packaging).

Build date 11 Sep 2025

Above information is reliable, but does not constitute warranty.

ICHEMCO srl
via 11 Settembre, 5 - 20012 CUGGIONO (MI) - ITALY
Phone: +39 02 97243.1 - info@ichemco.it - www.ichemco.it