ichemco
Developing Chemical Excellence

member of Afera

CERTIFIED MANAGEMENT SYSTEMS
CERTIQUALITY
UNI EN ISO **9001:2015**
UNI EN ISO **14001:2015**
UNI ISO **45001:2018**

Antiox W 54

Description

ANTIOX W 54 is a 40% TS aqueous dispersion of a sterically hindered phenolic antioxidant. ANTIOX W 54 protects the substrates against thermo-oxidative degradation during manufacturing, processing and end-use.

Application

Antiox W 54 is recommended for the stabilization of PVC. It is also a very effective antioxidant for natural and synthetic latex water borne adhesives.

Technical Specifications

Method of analysis	UoM	Standard
1. Total Solids	%	40 ± 1
8. pH		5.2 ÷ 7.4
Solvents		water

Handling

Add ANTIOX W 54 directly in the water dispersion. Recommended quantity for water borne adhesives is 0,2-1%.

Packaging

The product is supplied in plastic tanks (20 kg); plastic drums (50 kg); iron drums (200 kg); IBC containers (900 kg).

Storing

Store at temperatures between + 5 and + 40°C. Protect from freezing. If stored for a prolonged time, stir well before use.

Use within 12 months from production date (unopened and in the original packaging).

Above information is reliable, but does not constitute warranty.

ICHEMCO srl
via 11 Settembre, 15 - 20012 CUGGIONO (MI) - ITALY
Phone: +39 02 97243.1 - info@ichemco.it - www.ichemco.it