Release FR 100 V1

(Provisional)

Description

RELEASE FR 100 V1 is a release agent that, besides the normal unwinding properties, provides a suitable surface for the anchorage of the PU foam in the so-called "freezer tapes".

Application

RELEASE FR 100 V1 is designed for the production of PE and aluminium tapes, which are commonly used for blocking and protecting the coils in the refrigerator assemblage.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	99±1
5. Melting Range	°C	60

Handling

RELEASE FR 100 V1 has to be diluted at 0.5-2% in a blend of toluene/ isopropyl alcohol (85/15).
The solution of RELEASE FR 100 V1 can be applied on the film by Mayer-bar, rotogravure or any other low viscosity coating system. The coating weight depends upon the adhesive. Recommended range is 0.2-0.5 g/sqm dry. Once diluted, it can be applied at room temperature and must be well dried.

Packaging

The product is supplied in fibre drums (20 kg).

Storing

Store in sealed containers, well protected from direct sunlight. If the solution of RELEASE K 100 V1 is stored for a prolonged time, we recommend to stir it before using.

Use within 24 months from production date (unopened and in the original packaging).

Build date 11 Sep 2025

Above information is reliable, but does not constitute warranty.

ICHEMCO srl
via 11 Settembre, 5 - 20012 CUGGIONO (MI) - ITALY
Phone: +39 02 97243.1 - info@ichemco.it - www.ichemco.it