# Primer PP 10 Eco

*(Provisional)*

## Description

PRIMER PP 10 ECO is a solvent borne primer for polyolefinic films and natural rubber based adhesives.

It does not contain aromatic solvents.

## Application

PRIMER PP 10 ECO has been developed for the application of treated polyolefin films.

## Technical Specifications

| Method of analysis | MU | Standard |
|---|---|---|
| 1. Total Solids Solvents | % | 10±0.50 cyclohexane |

## Handling

The application systems can be reverse-roll and Mayer bar.

PRIMER PP 10 ECO must be activated prior to its use by adding CURING AGENT CH (0,6-1%) or CURING AGENT D (1-1.5%), the pot-life of the product is reduced as crosslinking starts immediately after the addition of the curing agent.

Stir well after activation. Apply 0.5-0.6 g dry/sqm. If necessary, the product can be diluted with cyclohexane or toluene.

## Packaging

The product is supplied in iron drums (165 kg).

## Storing

Store the product at room temperature, protected from direct sunlight and humidity. Stir well before use.

Use within 12 months from production date (unopened and in the original packaging).

Build date 11 Sep 2025



*Above information is reliable, but does not constitute warranty.*

**ICHEMCO srl**
via 11 Settembre, 5 - 20012 CUGGIONO (MI) - ITALY
Phone: +39 02 97243.1 - info@ichemco.it - www.ichemco.it