Primer MT2

Description

PRIMER MT2 is a primer for impregnated kraft paper for masking tape . It is based on a synergic blend of natural/synthetic latices, modified with stabilizers, resins and additives.

Application

PRIMER MT2 achieves a very good adhesion between the impregnated paper and the adhesive mass, either solvent or hot-melt based (natural and SIS rubber). It is recommended for the coating of hot-melt adhesives or aliphatic solvent borne adhesives.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	46±1
3. Brookfield Viscosity 25°C	mPa.s	50 - 200 (1)
8. pH		9 - 10

(1) No 1 RV; 50 RPM

Handling

Dilution: it depends upon the coating system, the product can be diluted with water, when a lower viscosity is required. If required it can be thickened with acrylic thickeners; the product is also available at higher viscosity.

Coating weight: 2,0 -3,0 g/sqm dry.

Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

Storing

Product must be stored at temperatures between +5°C and +40°C. Avoid freezing temperatures.

Use within 6 months from production date (unopened and in the original packaging).

Build date 11 Sep 2025

Above information is reliable, but does not constitute warranty.

ICHEMCO srl
via 11 Settembre, 5 - 20012 CUGGIONO (MI) - ITALY
Phone: +39 02 97243.1 - info@ichemco.it - www.ichemco.it